

FLIR B365


Infrared Camera with Thermal Fusion, Delta T and Interchangeable Lens

FLIR B365 is a feature-rich camera for the professional thermographer conducting building inspections and energy declaration surveys. B365 includes many useful features such as Picture in Picture, Zoom, Thermal Fusion, Instant Reports, and much more.

- 50 mK thermal sensitivity
- IR resolution 320 x 240 pixels
- Digital camera, 3.1 Mp with LED lights
- 4x digital zoom
- Delta T - Differential temperature
- Instant Reports
- Sketch & Markers
- MeterLink™




Multifunction 3.5" Touch Screen



Picture in Picture (PiP)



120° lens rotation



Thumbnail Image Gallery



FLIR B365 Features

- **High Resolution IR Images** — 320 x 240 pixels infrared resolution, NETD 50 mK
- **Digital Camera** — 3.1 Megapixels with built-in LED lights provides sharp images regardless of lighting conditions
- **Temperature Range** — Measures from -20 °C to +120 °C targeting building applications
- **Insulation alarm** — Shows the insulation performance of the building structure
- **Dew point alarm** — Alerts you to the areas where there is a risk of condensation
- **Zoom** — 4x continuous digital zoom for capturing small details
- **Picture in Picture (PiP)** — Displays resizable IR image super-imposed over a digital image
- **Thermal Fusion** — Merging visual and infrared images, allows for easier identification and interpretation of infrared images
- **Laser Pointer** — Pinpoints the hot spot on the IR image with the real physical target
- **Annotations** — Add text/voice/sketch comments and image markers via touch screen or headset
- **± 2% Accuracy** — Reliable temperature measurement
- **Thumbnail Image Gallery** — Allows quick search of stored images
- **MeterLink™** — Wirelessly transmit data from clamp or moisture meter to your infrared camera
- **Delta Temperature** — Automatic calculation of temperature difference between two measurement tools
- **Instant Reports** — Create instant report directly in camera, easily copy report to USB
- **Copy to USB** — Upload images and measurement findings to USB stick
- **IR Window Auto-Correction** — Automatic sensitivity adjustment when inspecting high voltage through safety IR windows
- **Li-Ion Rechargeable Battery** — Replaceable battery lasts > 4 hours of continuous use
- **Interchangeable Optics** — Standard 25° lens and optional 15°, 45° and 90° lenses
- **Standard SD Card** — Stores more than 1000 radiometric JPEG images
- **Includes** — SD Memory Card, Li-Ion rechargeable battery with 100-260V AC adaptor/charger, 2-bay battery charger, QuickReport software, USB Mini-B cable, video cable, sun shield, stylus pen & headset, camera lens cap, and transport case




What is MeterLink™?


MeterLink displays and documents readings from your Extech moisture- or clamp meter directly on your infrared image using Bluetooth wireless connection.

MeterLink, a FLIR industry-first technology, will: greatly improve your diagnostics, save time annotating readings, eliminate data errors, and add more customer value to your reports.


Applications



Building: Water and mildew in wall



Building: Heat Loss



Electrical: Hot Fuses



Building: Heat Loss



FLIR B365 Specifications

Imaging and optical data

Field of view (FOV)	25° × 19° / 0.4 m
Thermal sensitivity/NETD	50 mK
Image frequency	9 Hz or 30 Hz
Focus	Manual/Automatic
Zoom	1–4x continuous, digital zoom, including panning
Spectral range	7.5–13 μm
IR resolution	320 × 240 pixels

Image presentation

Display	Built-in touch screen, 3.5" color LCD
Image modes	IR image, visual image, thermal fusion, picture in picture, thumbnail gallery
Thermal Fusion	IR image shown within temp interval on visual image
Picture in Picture	Resizable and movable IR area on visual image

Measurement

Object temperature range	–20 °C to +120 °C
Accuracy	±2°C

Measurement analysis

Spotmeter	5
Area	5 boxes with max./min./average
Isotherm	Detect high/low temperature/interval
Difference temperature	Delta temperature between measurement functions or reference temperature
Measurement function alarm	Audible/visual alarm (above/below) on spotmeter, box or difference temperature
Screening	Difference temperature alarm, audible
Dew point alarm	1 dew point alarm
Insulation alarm	1 insulation alarm

Set-up

Color palettes	BW, BW inv, Iron, Rain
----------------	------------------------

Storage of images

Image storage	Standard JPEG, including measurement data, on memory card
Image storage mode	IR/visual images; simultaneous storage of IR and visual images

Image annotations

Voice	60 seconds
Text	Text from predefined list or soft keyboard on touch screen
Image marker	4 on IR or visual image
Sketch	From touch screen
MeterLink	Connect Extech Clamp Meter EX845/Moisture Meter M0297 via Bluetooth®

Digital camera

Built-in digital camera	3.1 Mpixel (2048 × 1536 pixels), and LED lights
-------------------------	---

Physical data

Camera weight, incl. battery	0.88 kg
Camera size (L × W × H)	106 × 201 × 125 mm



Software

- FLIR QuickReport™**
 Allows the user to organize, analyze and present infrared image data in a report. Delivered with your FLIR camera.
- FLIR BuildIR™**
 A powerful yet easy-to-use software designed to visualise and quantify building related issues.

Accessories

- Pouch
- Extra battery
- Battery charger
- Car charger
- Selection of lenses



Training

FLIR cooperates with Infrared Training Centre, an independent, ISO certified, worldwide training facility. ITC offers infrared training, certifications accepted by many standardization organizations, and specialized instruction in various application areas. For more info visit www.infraredtraining.com

Specifications and prices subject to change without notice.

Copyright © 2010 FLIR Systems. All right reserved including the right of reproduction in whole or in part in any form.

FLIR Systems, Sweden

World Wide Thermography Center
 Rinkebyvägen 19 - PO Box 3
 SE-182 11 Danderyd
 Tel: +46 (0)8 753 25 00
 e-mail: sales@flir.se

www.flir.com/thg



Authorised FLIR dealer: